

SPECIFICATIONS



0 - 2,500 RPM

Model 6823	
Capacities	
Drywall screw	6 mm
Self drilling screw	6 mm
Driving shank	6.35 mm Hex
Continuous rating	
Input	570 W
No load speed	0 - 2,500 RPM
Overall length	286 mm
Net weight	1.5 kg
Power supply cord	* 2.5 m



0 - 4,500 RPM

Model 6824	
Capacities	
Drywall screw	5 mm
Self drilling screw	6 mm
Driving shank	6.35 mm Hex
Continuous rating	
Input	570 W
No load speed	0 - 4,500 RPM
Overall length	275 mm
Net weight	1.4 kg
Power supply cord	* 2.5 m

* For European countries, 4 m



0 - 6,000 RPM

Model 6825	
Capacities	
Drywall screw	4 mm
Driving shank	6.35 mm Hex
Continuous rating	
Input	570 W
No load speed	0 - 6,000 RPM
Overall length	275 mm
Net weight	1.4 kg
Power supply cord	* 2.5 m

Double Insulation

Drywall Screwdriver

Model 6823 (No load speed 0—2,500 RPM)
6824 (No load speed 0—4,500 RPM)
6825 (No load speed 0—6,000 RPM)

0 - 6,000 RPM - Fastest Drywall Screwdriver Available
Metal Gear Housing for Heavy-Duty Performance
In-line Rubber Pistol Grip Design for Positive Control



NEW

STANDARD EQUIPMENT

Phillips Insert Bit	Size	Part No.
	2 - 25	784211-2
	1 pc.	

Magnetic bit Holder	Size	Part No.
	6.35 - 60	784807-9
	1 pc.	
	For European countries	

OPTIONAL ACCESSORIES

Phillips Insert Bit	Size	Part No.
	1 - 25	798313-8
	2 - 25	798312-0
	3 - 25	798314-6
	3 pcs/set	

Magnetic bit Holder	Size	Part No.
	6.35 - 76	784801-1
	6.35 - 60	784807-9

Makita Corporation
 3-11-8, Sumiyoshi-cho,
 Anjo, Aichi 446-8502, Japan

Note: The standard equipment for the tools shown may differ from country to country. Consult your local Makita catalogue or representative to know the standard equipment for Makita tools sold in your area.

PRINTED IN JAPAN Z15118-2 1999-12



The World's Fastest Drywall Screwdriver – 6,000 RPM (#6825)



Lightweight Cast Aluminum Gear Housing for durability

Retractable Belt Clip attaches to tool belt

Ergonomically Designed Rubber Grips for reduced operator fatigue and hand cramping "Fits like a glove"

Convenient Depth Adjustment

Lock-on Button large, recessed, and conveniently located

Standard Magnetic Bit Holder

Photo: Model 6825

Nose Piece is easy to install and remove

Silent Synchronized Pin Clutch dramatically reduces noise and wear

Extra Powerful Motor for continuous production work

Forward/Reverse Switch is conveniently located

Large Comfortable Trigger Switch is sealed for longer life

Leash Loop for attaching rope or cord to help prevent tool from falling



6000 rpm generates the ideal speed to fasten the screw into the drywall with almost no pressure applied by the drywaller when it comes to fastening a large number of screws.

Comparison List of No load Speed	
Competitors	(RPM)
	4,000
#6824	4,500
#6825	6,000

M a k i t a A d v a n t a g e



Nose Piece
Nose piece is easy to install and remove. Adjust sleeve for precise depth settings.



Carbon Brush
Quick and easy carbon brushes change.



Retractable Belt Clip
Retractable belt clip allows operation in tight areas.



Rubber Grips
Ergonomically designed for reduced operator fatigue and hand cramping "Fits like a glove."

