



A world's leading manufacturer of power tools

- Double Insulation
- Electronic Speed Control
- Bevel Cutting (45° left/right)
- Built-in Job Light
- Soft Start
- Dust Collecting
- Electric Brake

Slide Compound Miter Saw

255 mm (10") Model LS1013F

Equipped with fluorescent light for easy tracing cutting line!



1. Fluorescent Lamp on Flexible Arm

For a clear view of cutting lines, uses the inverter type that can throw bright light widely on and around workpiece.
(Service life of the lamp : 2,000 hours on average)

2. On-Off switch

On-Off switch for exclusive use of lamp works independently; independent of the On-Off switch for the motor.

Plus a clean, dust-free environment.

The blade cover is precision designed to assure saw dust is sent through a single chute into the dust bag or nozzle.
(Can be connected to vacuum cleaner.)

Workpieces in the dimness...

➡➡➡

...can be lit brightly for clear view of cutting lines.

Standard equipment

Dust bag assembly	Vise assembly (Vertical vise)
Socket wrench 13	T.C.T Saw blade
Holder 255	Switch button (spare)
Triangular rule	

Items of standard equipment may differ from country to country.

Optional accessories

Fluorescent Lamp

Specifications

Blade diameter	255 mm - 260 mm (10"-10-1/4")
Max. cutting capacities with	255 mm (10") blade
at 90°	91 mm x 305 mm (3-5/8" x 12")
at 45°	91 mm x 215 mm (3-5/8" x 8-1/2")
Continuous rating (Input)	1,430 W
No load speed	3,700 min ⁻¹ (rpm)
Overall dimensions (L x W x H)	760 mm x 520 mm x 625 mm (30" x 20-1/2" x 24-5/8")
Net weight	21 kg (46.3 lbs)
Power supply cord	2.5 m (8.2 ft.)

Specifications may differ from country to country.

