



Adapter for USB ADP06



Compact adapter for USB compatible devices



Belt clip



ON-OFF switch
activates or deactivates USB output.

Strap hole








Powered by All Makita Slide 10.8V Li-ion batteries

Battery and charger are sold separately.

USB output port with caps

- enables to charge a mobile device
- can be used as a power source of Laser level by using a power supply cable.
- Type A USB socket for DC5V/ 2.1A USB output

Slide Li-ion Battery & Charger Time Reference, Compatibility Chart

	 BL1015 10.8V 1.5Ah	 BL1020B 10.8V 2.0Ah with Battery fuel gauge	 BL1040B 10.8V 4.0Ah with Battery fuel gauge
 DC10SA for 10.8V	22min	30min	60min
 DC10WC for 10.8V	50min	70min	130min

Adapter for USB	
ADP06	
USB port	1 (A type DC5V/ 2.1A)
Dimensions (L x W x H)	without battery: 80x53x38mm (3-1/8"x2-1/16"x1-1/2")
Net weight	BL1040B: 0.44kg (1.0lbs) BL1015: 0.28kg (0.6lbs)
<i>Battery and charger are sold separately.</i>	
<small>weight according to EPTA-Procedure 01/ver.2.1</small>	
<small>Items of standard equipment and specifications may vary by country or area.</small>	

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201606