



Satisfy Professional's Needs

Cordless Hammer Driver Drill Cordless Driver Drill



**Lightweight
14.4V / 18V
Driver Drills**

18V
Hammer Driver Drill
BHP453

LXT
LITHIUM-ION

High durability and high maneuverability



High / Low speed change lever

Single sleeve keyless chuck
allows for easy bit installation/removal with one hand.

Drill Mode + 16 Torque Settings

All metal gear construction

Variable Speed Control Switch

Ergonomically designed rubberized soft grip
provides comfortable grip and more control while minimizing hand fatigue and pain.

Lightweight battery
BL1415/ BL1815
14.4V 1.5Ah: BHP343, BDF343

18V 1.5Ah: BHP453, BDF453
















Higher capacity battery
BL1430/ BL1830
14.4V 3.0Ah: BHP343, BDF343

18V 3.0Ah: BHP453, BDF453

Charger DC18RA:
approx. 22 minutes charging time (BL1830, BL1430)
approx. 15 minutes charging time (BL1815, BL1415)

Charger DC18SD:
approx. 60 minutes charging time (BL1830, BL1430)
approx. 30 minutes charging time (BL1815, BL1415)

Photo: BHP453 (1.5Ah battery)

		BHP343 10mm (3/8")	BHP453 13mm (1/2")		
		BDF343 10mm (3/8")	BDF453 13mm (1/2")		
 Variable Speed  Reversing  Mechanical 2-Speed  Electric Brake  Keyless Chuck  Torque Setting 16  Carrying Case					
					
Capacity	Steel :	10mm (3/8")	13mm (1/2")	10mm (3/8")	13mm (1/2")
	Wood :	25mm (1")	36mm (1-7/16")	25mm (1")	36mm (1-7/16")
	Masonry :	10mm (3/8")	13mm (1/2")	-	-
Impacts per minute (ipm)	Hi / Lo	0-19,500 / 0-6,000	0-19,500 / 0-6,000	-	-
No load speed (rpm)	Hi / Lo	0-1,300 / 0-400	0-1,300 / 0-400	0-1,300 / 0-400	0-1,300 / 0-400
Max. fastening torque (N.m)	Hard / Soft	36 / 20	42 / 27	36 / 20	42 / 27
Dimensions (mm) (L x W x H)	battery: 1.5Ah	211 x 79 x 226 (8-5/16" x 3-1/8" x 8-7/8")	232 x 79 x 227 (9-1/8" x 3-1/8" x 8-15/16")	192 x 79 x 226 (7-9/16" x 3-1/8" x 8-7/8")	214 x 79 x 227 (8-7/16" x 3-1/8" x 8-15/16")
	3.0Ah	211 x 79 x 243 (8-5/16" x 3-1/8" x 9-9/16")	232 x 79 x 244 (9-1/8" x 3-1/8" x 9-5/8")	192 x 79 x 243 (7-9/16" x 3-1/8" x 9-9/16")	214 x 79 x 244 (8-7/16" x 3-1/8" x 9-5/8")
Net weight	battery: 1.5Ah	1.4kg (3.1lbs)	1.7kg (3.7lbs)	1.3kg (2.9lbs)	1.6kg (3.5lbs)
	3.0Ah	1.6kg (3.5lbs)	1.9kg (4.2lbs)	1.5kg (3.3lbs)	1.8kg (4.0lbs)
Voltage		14.4V	18V	14.4V	18V
Standard Equipment Fast Charger, Battery Cartridge, (+) (-) Bit					

Items of standard equipment and specifications may differ by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN Z23401-2 AI-AJ