

Cordless Percussion Driver Drill

BHP440, BHP450

436

- Mechanical 2-Speed
- Variable Speed
- Reversing
- Keyless Chuck
- Electric Brake
- Torque Setting 16
- Carrying Case
- Built-in Job Light



14.4V: BHP440

18V: BHP450



Fast Charger, Battery Cartridge (2pcs.), +Bit (2pcs.)

	BHP440	BHP450
Capacity	Steel 13mm (1/2")	13mm (1/2")
	Wood 27mm (1-1/16")	27mm (1-1/16")
	Masonry 13mm (1/2")	13mm (1/2")
Blows per minute / No load speed	Hi: 0-21,000 / 0-1,400rpm Lo: 0-6,000 / 0-400rpm	Hi: 0-21,000 / 0-1,400rpm Lo: 0-6,000 / 0-400rpm
Max. fastening torque	Hard / Soft : 41 / 25N.m	Hard / Soft : 41 / 25N.m
Dimensions (L x W x H)	204 x 79 x 242mm (8" x 3-1/8" x 9-1/2")	204 x 79 x 244mm (8" x 3-1/8" x 9-5/8")
Net weight	1.7kg (3.7lbs)	1.8kg (4.0lbs)
Voltage	14.4V	18V

Cordless Percussion Driver Drill

BHP441, BHP451

436

- Mechanical 3-Speed
- Variable Speed
- Reversing
- Keyless Chuck
- Electric Brake
- Torque Setting 16
- Carrying Case
- Built-in Job Light



14.4V: BHP441

18V: BHP451



Fast Charger, Battery Cartridge (2pcs.), +Bit (2pcs.), Side Grip, Depth Rod

	BHP441	BHP451
Capacity	Steel 13mm (1/2")	13mm (1/2")
	Wood 50mm (2")	65mm (2-9/16")
	Masonry 14mm (9/16")	16mm (5/8")
Blows per minute / No load speed	3rd: 0-25,500 / 0-1,700rpm 2nd: 0-9,000 / 0-600rpm 1st: 0-4,500 / 0-300rpm	3rd: 0-25,500 / 0-1,700rpm 2nd: 0-9,000 / 0-600rpm 1st: 0-4,500 / 0-300rpm
Max. fastening torque	Hard / Soft : 70 / 32N.m	Hard / Soft : 80 / 40N.m
Dimensions (L x W x H)	250 x 78 x 255mm (9-7/8" x 3-1/16" x 10")	250 x 78 x 257mm (9-7/8" x 3-1/16" x 10-1/8")
Net weight	2.1kg (4.6lbs)	2.2kg (4.9lbs)
Voltage	14.4V	18V

Cordless Driver Drill

BDF440, BDF450

436

- Mechanical 2-Speed
- Variable Speed
- Reversing
- Keyless Chuck
- Electric Brake
- Torque Setting 16
- Carrying Case
- Built-in Job Light



14.4V: BDF440

18V: BDF450



Fast Charger, Battery Cartridge (2pcs.), +Bit (2pcs.)

	BDF440	BDF450
Capacity	Steel 13mm (1/2")	13mm (1/2")
	Wood 27mm (1-1/16")	27mm (1-1/16")
No load speed	Hi: 0-1,400rpm Lo: 0-400rpm	Hi: 0-1,400rpm Lo: 0-400rpm
Max. fastening torque	Hard / Soft : 41 / 25N.m	Hard / Soft : 41 / 25N.m
Dimensions (L x W x H)	186 x 79 x 242mm (7-3/8" x 3-1/8" x 8")	186 x 79 x 244mm (7-3/8" x 3-1/8" x 9-5/8")
Net weight	1.6kg (3.5lbs)	1.7kg (3.7lbs)
Voltage	14.4V	18V

Cordless Driver Drill

BDF441, BDF451


436

- Mechanical 3-Speed
- Variable Speed
- Reversing
- Keyless Chuck
- Electric Brake
- Torque Setting 16
- Carrying Case
- Built-in Job Light



14.4V: BDF441

18V: BDF451



Fast Charger, Battery Cartridge (2pcs.), +Bit (2pcs.), Side Grip

	BDF441	BDF451
Capacity	Steel 13mm (1/2")	13mm (1/2")
	Wood 50mm (2")	65mm (2-9/16")
No load speed	3rd: 0-1,700rpm 2nd: 0-600rpm 1st: 0-300rpm	3rd: 0-1,700rpm 2nd: 0-600rpm 1st: 0-300rpm
Max. fastening torque	Hard / Soft : 70 / 32N.m	Hard / Soft : 80 / 40N.m
Dimensions (L x W x H)	238 x 78 x 255mm (9-3/8" x 3-1/16" x 10")	238 x 78 x 257mm (9-3/8" x 3-1/16" x 10-1/8")
Net weight	2.0kg (4.4lbs)	2.1kg (4.6lbs)
Voltage	14.4V	18V

Items of standard equipment and specifications may differ from country to country.



Cordless Percussion Driver Drill

BHP440, BHP441 BHP450, BHP451

Cordless Driver Drill

BDF440, BDF441 BDF450, BDF451



LITHIUM-ION

MAKSTAR LITHIUM-ION

LIGHTWEIGHT & COMPACT



40% lighter

MAKITA 14.4V, 18V Ni-MH 3.0Ah



MAKITA 14.4V, 18V Li-ion 3.0Ah

- ANYTIME CHARGE NO MEMORY EFFECT
- LONGTIME STORAGE LOW SELF DISCHARGE
- SHOCK ABSORBING HEAVY DUTY PACK
- FIRM HOLDING MULTI CONTACT

MAKSTAR Battery Checker

MAKSTAR Battery Checker detects the number of charges, and diagnoses the condition of MAKSTAR Ni-MH/ Li-ion batteries.

This equipment reads the history of the battery from the built-in CPU, finds how the operator treated the battery, and gives the right advice to

MAXIMIZE THE LIFE OF THE BATTERY.

- * It can be also used for simple-checking conventional Makita batteries, using the adapter which is included with the Battery Checker.
- * PC is not included in the set.
- * Battery Checker works with Makita Makstar charger DC24SA, DC24SC and a PC.



Makita Corporation

3-11-8, Sumiyoshi-cho, Anjo, Aichi 446-8502, Japan

PRINTED IN JAPAN Z15195-2 2005-11

