



Rechargeable Flashlight BML800

Satisfy Professional's Needs



COMPACT DESIGN HEAD LIGHT for high maneuverability

Can be used as a stationary lamp by attaching the head light section to the battery holder section.



1.6W BRIGHT LED

Illuminance: 2,000lx* or more

*Illuminance: measured in ø 20mm circle at the center of an illuminated field 1m in front of the light source

20 hours

Long continuous illumination

on a single full battery charge (with 18V-3.0Ah battery)

IPX4 waterproof design

(Head light section only)

resists splashing water such as a sudden shower, etc.



Belt clip

enables to hook Battery holder on waist belt, etc.



Battery

Higher capacity
BL1830 18V-3.0Ah



Lightweight
BL1815 18V-1.3Ah



Higher capacity
BL1430 14.4V-3.0Ah



Lightweight
BL1415 14.4V-1.3Ah



Charger

DC18RA / DC18RC

Charging time
BL1815, BL1415: 15minutes
BL1830, BL1430: 22minutes



DC18SD

Charging time
BL1815, BL1415: 30minutes
BL1830, BL1430: 60minutes



Rechargeable Flashlight **BML800**

Continuous use (hours)	20-3.0Ah, 8.5-1.3Ah (18V) / 17-3.0Ah, 7.5-1.3Ah (14.4V)
Dimensions (L x W x H)	Head light section : 55x55x55mm (2-3/16"x2-3/16"x2-3/16") Battery holder section : 133x76x71mm (5-1/4"x3"x2-13/16") with BL1415 (14.4V-1.3Ah) 133x76x88mm (5-1/4"x3"x3-1/2") with BL1430 (14.4V-3.0Ah) 151x76x71mm (5-15/16"x3"x2-13/16") with BL1815 (18V-1.3Ah) 151x76x88mm (5-15/16"x3"x3-1/2") with BL1830 (18V-3.0Ah)
Net weight*	0.58kg (1.3lbs) with BL1415, 0.77kg (1.7lbs) with BL1430 0.64kg (1.4lbs) with BL1815, 0.86kg (1.9lbs) with BL1830

Standard Equipment : Rubber Head Strap, Battery and Charger are sold separately.

*Weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BB-BA