



Cordless Impact Driver BTD135

Satisfy Professional's Needs



1.5Ah Battery
BL1415



3.0Ah Li-ion Battery

Lightweight at only
320g

LITE 1.5Ah

Lithium-ion Slim Battery



Very compact body and lightweight design.



Lightweight :
1.2kg (2.6lbs)

Compact : 145mm (5-3/4")

Compact :
217mm (8-1/2")

One-touch bit installation
No need to pull bit sleeve for bit installation

Phosphorescent bumper
Convenient in dark place.

LED Job Light with afterglow function
Light can be turned on before tool starts by pulling the trigger slightly.



Variable speed control by trigger

Belt clip
(optional accessory)



Lightweight battery BL1415
14.4V 1.5Ah

Higher capacity battery BL1430
14.4V 3.0Ah
(optional accessory)



Fast Charger
DC18RA Charging time
BL1415: 15minutes
BL1430: 22minutes



High power-to-weight ratio obtained by employing 4 -pole motor



Ergonomically designed handle with rubberized soft grip
Provides more comfort and control while minimizing hand fatigue and pain.



Cordless Impact Driver

- Variable Speed
- Reversing
- Electric Brake
- Carrying Case
- Built-in Job Light



BTD135

440

Capacity	
Machine screw	M4 - M8 (5/32" - 5/16")
Standard bolt	M5 - M14 (3/16" - 9/16")
High tensile bolt	M5 - M12 (3/16" - 1/2")
Coarse thread (in length)	22 - 125mm (7/8" - 4-7/8")
Driving shank	6.35mm (1/4") Hex
Impacts per minute (ipm)	0-3,200
No load speed (rpm)	0-2,400
Max. fastening torque	145N.m (1,280in.lbs)
Dimensions (L x W x H)	145 x 79 x 217mm (5-3/4" x 3-1/8" x 8-1/2")
Net weight	1.2kg (2.6lbs)
Voltage	14.4V

Standard Equipment Fast Charger, Battery Cartridge

Items of standard equipment and specifications may differ by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN Z23402-2 AI-AI