



Satisfy Professional's Needs

Cutter  
4102NH 110mm (4-3/8")

# Bevel Cut up to 45 degrees



# 110mm (4-3/8") Cutter



Switch trigger with dust cover

Depth Guide for adjustment of cutting depth

Front Grip for stable operation

Bevel angle scale

Guide rule (option) can be attached from both sides.



## Bevel Cutting



Hinge portion of blade case is assembled with screw and hex nut for easy disassembling.

Easy alignment of the diamond wheel with the cutting line:  
By aligning the end of base at 0 degrees cutting

By aligning the top of the U-notch at 45 degrees bevel cutting

Water supply unit

Easy replacement of the diamond wheel  
Screw can be loosened or tightened with either hex wrench or hex socket wrench.

## Cutter

## 4102NH 110mm (4-3/8")

303

Double Insulation

Bevel Cutting



Continuous rating Input Capacity	1,300W at 90 degrees : 32mm (1-1/4") at 45 degrees : 21mm (13/16")
Blade diameter	110mm (4-3/8")
No load speed (rpm)	13,000
Dimensions (L x W x H)	243 x 208 x 166mm (9-9/16" x 8-3/16" x 6-1/2")
Net weight	2.9kg (6.4lbs)
Power supply cord	2.5m (8.2ft)

### Standard Equipment

Wrench, Hex Wrench, Water Plug & Tube  
(Tool does not come with diamond wheel.)

Items of standard equipment and specifications may differ by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN Z23364-2 AI-AD