



Satisfy Professional's Needs

Drywall Screwdriver series

2,500min⁻¹

FS2200
FS2300



Photo: FS2300

4,000min⁻¹

FS4000
FS4200
FS4300



Photo: FS4200

6,000min⁻¹

FS6200
FS6300
FS6300R



Photo: FS6300

**Easy handling and
High maneuverability**

Compact design

well balanced for easy handling and high maneuverability



Aluminum gear housing

FS4000: plastic gear housing

One touch locator

Easy to install or remove

Ingenious exhaust vents

Exhaust air does not blow dust and debris around when the tool is used close to floor level.

LED job light

convenient for operation in dark job sites (not available FS4000)



Locator holder

convenient for temporary storage of locator during operation



Locator

Reversing switch

Variable speed control by trigger switch

Photo: FS6300

Bit holder

Spare bit can be stored.

More durable belt clip

composed of a sheet metal sandwiched between plastic layers for added strength

Best possible tool body for screwdriving

ergonomically designed to:

- minimize hand fatigue and pain even in long continuous operation.
- give maximum power thrust.
- allow for much smoother and easier trigger pull.




Rubberized soft grip

provides comfortable grip and more control while minimizing hand fatigue and pain.

Removable power supply cord (FS6300R only)

Length: 4m(13.1ft)



	FS2200	FS2300	FS4000/ FS4200	FS4300	FS6200	FS6300/ FS6300R
Capacity Drywall screw (mm)	5	5	5	5	4	4
No load speed (rpm)	0 - 2,500	0 - 2,500	0 - 4,000	0 - 4,000	0 - 6,000	0 - 6,000
Silent clutch	No	Yes	No	Yes	No	Yes
Net weight *(kg)	1.6	1.6	1.3 / 1.4	1.4	1.4	1.4

*weight according to EPTA-Procedure 01/2003

Drywall Screwdriver FS2200/ FS2300/ FS4000/ FS4200/ FS4300/ FS6200/ FS6300/ FS6300R 419

- Double Insulation
- Variable Speed
- Reversing
- Built-in Job Light (not available FS4000)



FS2200



FS4200



FS6300

	FS2200/ FS2300	FS4000/ FS4200/ FS4300	FS6200/ FS6300/ FS6300R
Continuous rating Input	570W	570W	570W
Capacity Drywall screw:	5mm (3/16")	5mm (3/16")	4mm (5/32")
Self drilling screw:	6 mm (1/4")	6 mm (1/4")	-
Driving shank (Hex.)	6.35 mm (1/4")	6.35mm (1/4")	6.35mm (1/4")
No load speed (rpm)	0-2,500	0-4,000	0-6,000
Dimensions (L x W x H)**	FS2200: 287 x 70 x 207mm (11-1/4" x 2-3/4" x 8-1/8") FS2300: 290 x 70 x 207mm (11-3/8" x 2-3/4" x 8-1/8")	FS4000/ FS4200/ FS6200: 269 x 65 x 207mm (10-5/8" x 2-9/16" x 8-1/8") FS4300/ FS6300/ FS6300R: 279 x 65 x 207mm (11" x 2-9/16" x 8-1/8")	
Net weight*	FS2200/ FS2300: 1.6kg (3.5lbs)	FS4200/ FS4300/ FS6200/ FS6300/R: 1.4kg (3.1lbs)	FS4000: 1.3kg (2.9lbs)
Power supply cord	2.5m (8.2ft) (FS6300R: 4.0m (13.1ft))		

Standard Equipment Phillips Insert Bit (2pcs.), Magnetic Bit Holder

**for countries providing noise suppressor and connect bit 60
*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN Z15234-2 AJ-BA