



Angle Grinder
 GA7030/ S, GA7040/ S 180mm (7")
 GA9030/ S, GA9040/ S 230mm (9")

Outstanding Durability



Option

Anti Vibration AVT Grip Part No. 194290-6

Loop Handle Part No. 192619-0

Plastic carrying case Part No. 824755-1

Dust Collecting Wheel Guard Part No. 194044-1

Dust Covers Part No. 194289-1
 Protect motor from metal dust.

Angle Grinder GA7030/ S/ GA7040/ S 180mm (7") / GA9030/ S/ GA9040/ S 230mm (9") 204

- Double Insulation
- Soft Start (GA7030S/ GA7040S/ GA9030S/ GA9040S)
- Torque Limiter



	GA7030/ GA7030S	GA7040/ GA7040S	GA9030/ GA9030S	GA9040/ GA9040S
Continuous rating Input	2,400W	2,600W	2,400W	2,600W
Capacity (Depressed center wheel)	180mm (7")	230mm (9")	230mm (9")	230mm (9")
Hole dia.	22.23mm (7/8")	22.23mm (7/8")	22.23mm (7/8")	22.23mm (7/8")
No load speed	8,500rpm	6,600rpm	6,600rpm	6,600rpm
Dimensions (L x W x H)	511mm x 200mm x 140mm (20-1/8" x 7-7/8" x 5-1/2")	511mm x 249mm x 140mm (20-1/8" x 9-3/4" x 5-1/2")	511mm x 249mm x 140mm (20-1/8" x 9-3/4" x 5-1/2")	511mm x 249mm x 140mm (20-1/8" x 9-3/4" x 5-1/2")
Net weight*	6.0kg (11.2lbs)	6.4kg (14.0lbs)	6.3kg (13.9lbs)	6.6kg (14.6lbs) GA9040 6.7kg (14.8lbs) GA9040S
Power supply cord	2.5m (8.2ft)	2.5m (8.2ft)	2.5m (8.2ft)	2.5m (8.2ft)

Standard Equipment: Lock Nut wrench, Grip (Tool does not come with depressed center wheel)

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.



Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BD-AJ

