

Water Supply Function series

Satisfy Professional's Needs



Angle Sander
PK5011C 125mm (5")

Angle Sander



PK5001C

Stone Polisher



PW5001C

Stone Polisher



PW5000C

Both hands held



Water Supply Function

Accessories

Offset diamond wheel (wet)		Spindle thread: M14 x 2	
Type	Grit	Part No.	
	-	D-36843	
	36	D-37247	
	60	D-37253	
	120	D-37269	
	220	D-37275	
	400	D-37281	

Dust cover set	
Part No.	195773-9

Offset dia wheel cover set	
Part No.	195774-7

Head cover	
Part No.	418529-6

Rubber pad (For abrasive disc)	
Part No.	743015-1

Protector set	
Part No.	196028-5

Lock nut wrench, Lock nut release socket		
		Lock nut release socket (Square drive : 12.7mm)
Type	Size	Part No.
Lock nut wrench	28	782412-6
	35	782407-9
Lock nut release socket	28	194306-7
	35	194305-9

Grip	
Stick type	Anti Vibration type
Type	Part No.
Stick	152539-0
Anti Vibration	194543-3

Sanding lock nut	
Spindle thread	Part No.
M14 x 2 (DIN)	224515-5
5/8"	224517-1

Abrasive disc Disc type and use For stone (wet)			
Dia. (mm)	Grit	Per pkg.	Part No.
125	24	10	B-14526
125	50	10	B-14532
125	80	10	B-14548
125	120	10	B-14554



Angle Sander	PK5011C 125mm (5")	204
<ul style="list-style-type: none"> Variable Speed Constant Speed Soft Start 	<p>Continuous rating Input 1,600W Wheel diameter 125mm (5") No load speed (rpm) 2,000-5,500 Dimensions (L x W x H) 468x159x155mm (18-1/2"x6-1/4"x6-1/8") Net Weight* 3.8kg (8.4lbs) Power supply cord 4.0m (13.1ft)</p>	
<p>Standard Equipment: 125mm Dust Cover, Rubber Pad 115, Abrasive Discs 125, Side Grip, Head Cover, Lock Nut Wrench</p>		

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BC-AG



D-handle to operate machine with double hands for continuous operation



Water supply hose in handle



Water supply hose from rear connector to front body is laid in the handle housing, enabling operator to use this angle grinder with comfort and maneuverability.

Water resistant switch trigger



Rubber cover inside switch lever protects itself from wear and tear to prevent water ingress while keeping high switch operability.

Variable speed control



Variable speed control by dial provides an optimum speed for any sanding application.



Residual current device

Ribbed grip enables all finger tips to hold the handle more securely

Wheel cover for Abrasive disc

Rubber dust cover is used to protect operator from splash water.



Wheel cover for offset diamond wheel

Plastic wheel cover is used to protect operator from scattering water.



Electronic control

- Constant speed control; minimizes reduction in rotation speed under load, increasing operation efficiency.
- Soft start; suppresses start-up reaction.
- Electronic current limiter; protects motor from heat damage when the machine is overloaded.

4 Water supply holes



4 Water supply holes on spindle end feed water evenly to every channel of the polishing pad, protecting the pad from overheating and getting clogged with dust.

Water valve



Conveniently located water valve operable with the finger holding D-handle for easy water flow control in your hand

One-touch hose joint



Water supply hose can be connected with only one action.