






A world's leading manufacturer of power tools

 Double Insulation

 Soft Start

 Dust Collecting

Model KP312S

# Power Planer

312 mm (12-1/4") Model KP312, KP312S

*Planes up to 312 mm width  
stock at a single pass!*



**NEW**

## Power Planer



### Free from Uneven Planing

Uneven planing can be avoided by placing the tool's center of gravity to its center.

### 1. Increased Efficiency in Chip Ejection

Engineered in order not to be clogged even with wood chips of wet workpiece.

### 2. Front Roller

Allows the tool to move smoothly in repeated planing.

### 3. Plate Type Guide Rule

### 4. Foot



Installed on the rear of the tool for blades not to hit against workpiece or floor.

### 5. New Location for Power Supply Cord

Ideally located for preventing cord from being caught and rolled by the drum of the tool when the tool is taken back for another stroke.

### Soft Start Feature (Model KP312S only)

Prevents breakers from working unnecessarily in order not to interrupt operation, because generally, breakers at job sites have a small capacity.

### More Powerful Planing

Even hard wood can be easily planed.

### Overload Protector (Model KP312S only)

## Standard equipment

KP312	Part No.
Socket Wrench 9	782209-3
Triangular Rule	762001-3

Items of standard equipment may differ from country to country.

KP312S	Part No.
Hex Wrench 4	783219-3
Triangular Rule	762001-3
Nozzle Assembly	193733-5
Joint 70	181575-9

## Optional accessories

	Part No.
Nozzle Assembly	193733-5
Joint 70	181575-9
Planer Blade 312	B-02870

## Specifications

Planing width	312 mm (12-1/4")
Max. Planing depth	
Cutting width 0-150 mm	3.5 mm
150-240 mm	2 mm
240-312 mm	1.5 mm
No load speed	12,000 min <sup>-1</sup> (rpm)
Continuous rating	
Input	1,700 W (on 120V) (Model KP312) 2,200 W (on 230V) (Model KP312S)
Overall length	551 mm (21-3/4")
Net weight	19 kg (41.9 lbs)
Power supply cord	10 m (3.3 ft.)

## Dimension

