



Pneumatic Brad Nailer AF505

More Comfortable with Excellent Devices

Multi-directional Exhaust Port
Directs exhaust air away from operator. Rotatable 360 degrees by hand.

Rubber Bumpers
Protect the surface of work piece from scratches / damages.

Rubberized Grip

Tool Hook

Toolless Clearing of Jams
Enables quick removal of jammed nails.

Toolless Driving Depth Adjustment
Simply by turning the adjuster: in the direction of A for deeper setting, in the direction of B for shallower setting.

Remaining Nail View Windows
Allows to check remaining nails at a glance.

Pneumatic Brad Nailer		AF505	
	Dial Depth Adjusting	Capacity	Nail size : 15mm - 50mm (5/8" - 2")
	Carrying Case	Gauge	18 Ga
		Capacity	100nails
		Operating air pressure	60 - 115PSIG (4.0 - 8.0kgf / cm ² G)
		Dimensions (L x W x H)	260mm x 64mm x 237mm (10-1/4" x 2-1/2" x 9-3/8")
		Net weight	1.4kg (3.1lbs)
Standard Equipment Oil Supply, Safety Goggles, Nose Adapter			
<i>Items of standard equipment and specifications may differ from country to country.</i>			



Makita Corporation
3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan