



# Pneumatic Finish Nailer AF635

## Pneumatic Finish Nailer powered by pressure air 0.49 - 0.83 MPa.

**Anti-dry-fire mechanism**  
to prevent workpiece from damage

**Ergonomically designed  
rubber grip**  
with anti-slipping Rib provides  
more comfort and better control

**Air duster**  
By pushing the push button, air from  
compressor can be bypassed into the air  
duster nozzle to produce powerful air blast  
for sweeping up job site floor as well as  
workpiece.



**Protective bumpers**  
protect work piece and  
body from scratches or  
damage

**Hook**




**Remaining nail view window**

**Tool-less nail jam  
clearing**

**Easy-to see slim nose tip**  
allows quick and easy access to a  
desired fastening point.

**Tool-less Driving depth  
adjustment simply by  
turning a dial.**

### Pneumatic Finish Nailer AF635

-  Depth Adjusting
-  Carrying Case
-  Sequential or Bump-fire

<b>Capacity</b>	Length: 32 - 64 mm (1-1/4" - 2-1/2") Gauge: 15 Ga
<b>Operating Pressure</b>	0.49 - 0.83 MPa (70 - 120 PSI)
<b>Magazine Capacity</b>	100
<b>Dimensions (L x W x H)</b>	339x100x309mm (13-3/8"x3-15/16"x12-1/8")
<b>Net weight</b>	1.8 kg (4.0 lbs)

**Standard Equipment :**

Safety Goggles, Oil supply, Nose Adapter

weight according to EPTA-Procedure 01/ver.2.1

Items of standard equipment and specifications may vary by country or area.

## Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201608

