



Satisfy Professional's Needs

Cordless Clipped Head Framing Nailer GN900

Hoseless and High Performance



Easy Handling by using fuel gas as the power source, not using hoses and compressors



Protective bumpers

- Protect workpiece and the tool from scratches/ damage.
- Prevent the tool from slipping down on inclined surface such as a sloping roof.

Anti-Dry-Fire mechanism

Driving depth adjustment
(using Hex wrench)

Contact arm's top with anti-slip sure-grip spikes

Drives up to 3.3mm (0.131") in shank diameter with 90mm (3-1/2") of length 34 degree paper tape collated clipped head stick nail.

Magazine capacity: 44 nails (1 strip)

Note: Full round head nail cannot be used.

1,200 nails (approx.): the number of nails per Fuel cell

Ergonomically designed handle with rubberized soft grip
provides comfortable grip and more control while minimizing hand fatigue and pain.

Dual position hook
convenient for hanging from rafter or steel pipe

Uses 7.2V Li-ion battery BL7010
as the power source for ignition spark, gas mixing, air intake/exhaust and supply of cooling air.

Battery BL7010 **Charger DC075A**
Charging time: 30 min.

4000 nails (approx.): the number of nails on a single full battery charge

LED indication lamp with two convenient functions

- Battery power warning**
 - Blinking red warns that the remaining battery capacity is getting low.
 - Solid red warns that recharging is required.
- Trouble detection**
If trouble is detected, this function warns user by green/red alternate blinking and orange blinking.

Optional Accessories

Description	Part No. (Europe)	Part No. (Australia)	Size (mm) Length	Shank Dia	Fuel cell /box	Nails/ box	Part No.
Fuel Cell Twin Pack	194844-9	194845-7	Ring Bright				
Cleaner	242075-5	242076-3	51	2.9	3	3,300	194764-7
Lubricating Oil	242077-1	242078-9	51	2.9	1	1,100	194780-9
Cleaning Kit	194852-0	194853-8	63	2.9	3	3,300	194767-1
			63	2.9	1	1,100	194784-1
			75	3.1	2	2,200	194772-8
			Ring Galvanised				
			51	2.9	3	3,300	194765-5
			51	2.9	1	1,100	194782-5
			57	2.9	3	3,300	194766-3
			63	2.9	3	3,300	194768-9
			63	2.9	1	1,100	194785-9
			63	3.1	2	2,200	194770-2
			Ring Stainless				
			51	2.9	1	1,100	194799-8
			63	2.9	1	1,100	194800-9
			80	3.1	1	1,100	194801-7
			Ring Galvanised				
			63	2.9	1	1,100	194786-7
			63	3.1	2	2,200	194771-0
			63	3.1	1	1,100	194790-6
			75	3.1	2	2,200	194774-4
			75	3.1	1	1,100	194793-0
			83	3.1	1	1,100	194794-8
			Ring Hot Dip Galvanised				
			57	2.9	1	1,100	194783-3
			63	2.9	3	3,300	194769-7
			63	2.9	1	1,100	194786-7
			63	3.1	2	2,200	194771-0
			63	3.1	1	1,100	194790-6
			75	3.1	2	2,200	194774-4
			75	3.1	1	1,100	194793-0
			83	3.1	1	1,100	194794-8
			Smooth Bright				
			90	3.1	2	2,200	194776-0
			Smooth Galvanised				
			90	3.1	2	2,200	194777-8
			Smooth Hot Dip Galvanised				
			90	3.1	2	2,200	194778-6
			90	3.1	1	1,100	194797-2
			Unilock Hot Dip Galvanised				
			75	3.1	2	2,200	194775-2
			90	3.1	2	2,200	194779-4

Cordless Clipped Head Framing Nailer GN900

	Depth Adjusting	
	Carrying Case	
Capacity	Length : 50 - 90mm (2" - 3-1/2")	
Magazine Capacity	Diameter : 2.9-3.3mm	
Dimensions (L x W x H)	44 nails (1 strip)	
Net weight	321 x 108 x 368mm	
	(12-5/8" x 4-1/4" x 14-1/2")	
	3.4kg (7.5lbs)	
Standard Equipment	Hex Wrench, Safety Goggles	

Items of standard equipment and specifications may differ by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN Z23419-2 AI-BB