



Satisfy Professional's Needs

Circular Saw
5104S, 5104 260mm-270mm (10-1/4" - 10-5/8")

Ingenious Structure



and
High Power

Great for Heavy-duty Jobs

High Power 2,100W Motor



Continuous rating Input of Model 5104S

A Large ejection port for effective chip/sawdust exhaust.

B Joint (Dust nozzle) is attachable for connecting to vacuum cleaner. (Standard equipment for European countries)

C Rigid Aluminum Base provides smooth cutting because of toughness, bend resistance and lightweight.

D Super Joint System

E Adjustable top guide Aligns notches with cutting line for more precise cutting.

Large Guide Rule with scales
 · Enables accurate straight cut.
 · Can be attached from opposite side.

Super Joint System
 When saw blade is accidentally locked:
 • Absorbs shock to operator
 • Protects gears from damage
 Ensures smooth cutting feeling

Coil springs
 Gear
 Spindle

A Easy-to-read depth scales

B Large carrying handle

for easy transport to job site

Lock-off button prevents accidental starting

Hex wrench is storable

C Motor housing with flat end

convenient for replacing the saw blade

D Large view window

enables to check if blade edge is aligned with cutting line. Motor cooling air passes through and blows away sawdust.

E Bevel cuts up to 45 degrees

Indication Plate for adjusting bevel angle

0 - 45°

Circular Saw		5104S / 5104		203
Double Insulation		Continuous rating Input	2,100W (5104S) 1,700W (5104)	
Electric Brake		Capacity	at 90 degrees : 100mm (3-15/16") at 45 degrees : 73mm (2-7/8")	
Soft Start (5104S)		Blade diameter	270mm (10-5/8")	
Dust Collecting		No load speed	3,800rpm	
Super Joint System		Dimensions (L x W x H)	405 x 315 x 323mm (16" x 12-3/8" x 12-3/4")	
		Net weight	8.3kg (18.3lbs)	
		Power supply cord	2.5m (8.2ft)	
		Standard Equipment	Carbide-Tipped Saw Blade, Hex Wrench, Rip Fence (Guide Rule)	

Items of standard equipment and specifications may differ by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN Z23356-2 2007-12