



Satisfy Professional's Needs

Slide Compound Saw  
LS1018L, LS1017L 260mm (10-1/4")  
255mm (10")

# Big Cutting Capacity

310mm X 91mm  
(12" X 3-5/8")  
with 255mm (10") saw blade



Laser marker



Bevel range



LS1018L




LS1017L

# Higher Accuracy Cutting



## Laser marker

// Allows for easy cut line alignment.  
// Can be turned on/off with an independent switch.



**Rubberized soft grip**  
for more control

**Soft Start**  
for smooth start-ups

**Electric Brake**  
Stops the saw blade rotation  
for safe operation.

**Sliding sub fence**  
(Left side only)

**Holder can be attached**  
to both right and left sides  
for supporting long stock.

Photo: LS1018L

## Miter range of

60 degrees right and 47 degrees left  
with positive stops at 0, 15, 22.5, 31.6,  
45 degrees right and left

## Bevel range of:

// LS1017L:  
45 degrees left and  
5 degrees right



// LS1018L:  
45 degrees right and  
left



## Cutting capacities [Height x Width in mm] with 260mm (10-1/4") saw blade

\*with 255mm (10") saw blade

	<b>Bevel Cut at 45° left</b>	<b>Cross Cut</b>	<b>Bevel Cut at 45° right (LS1018L only)</b>
<b>Miter at 0°</b> 	 50 x 310 mm *50 x 305 mm (2" x 12")	 91 x 310 mm *91 x 305 mm (3-5/8" x 12")	 31 x 310 mm *31 x 305 mm (1-1/4" x 12")
<b>Miter at 45°</b> 	 left 50 x 200 mm *50 x 200 mm (2" x 7-7/8") right 50 x 220 mm *50 x 215 mm (2" x 8-1/2")	 91 x 220mm *91 x 215mm (3-5/8" x 8-1/2")	 31 x 220 mm *31 x 215 mm (1-1/4" x 8-1/2")
<b>Miter at 60°</b> 	—	 91 x 153 mm *91 x 150 mm (3-5/8" x 5-7/8")	—

## Slide Compound Saw

Double Insulation

Soft Start

Brake

Bevel Cutting 45 LR (LS1018L)

Bevel Cutting L45 R5 (LS1017L)

Laser Marker



## LS1018L, LS1017L

260mm (10-1/4")  
255mm (10")

JM23100183

### Continuous rating Input

1,430W

Max cutting capacity Blade diameter 260mm

at 0 degrees: 91 x 310mm

Bevel Cut at 45° left, Miter at 45° right

at 45 degrees: 91 x 220mm

Blade diameter 255mm

at 0 degrees: 91 x 305mm (3-5/8" x 12")

Bevel Cut at 45° left, Miter at 45° right

at 45 degrees: 91 x 215mm (3-5/8" x 8-1/2")

Blade diameter

255 - 260mm (10" - 10-1/4")

No load speed (rpm)

LS1018L: 4,300 LS1017L: 4,200

Dimensions (L x W x H)

LS1018L: 536 x 825 x 633mm (21-1/8" x 32-1/2" x 25")

LS1017L: 536 x 825 x 581mm (21-1/8" x 32-1/2" x 22-7/8")

Net weight\*

LS1018L: 19.9kg (43.9lbs) LS1017L: 19.5kg (43.0lbs)

Power supply cord

2.5m (8.2ft)

\*weight according to EPTA-Procedure 01/2003

Standard Equipment

Carbide-Tipped Saw Blade, Vertical Vise, Socket Wrench, Triangular Rule, Dust Bag, Holder Assembly

Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BA-AG