

ANNEX III	Item	Item on Website	Model	Model	Model	Model	Model	Model
			ML100/101	DML146	DML186	DML187	ML704/705	DML800
1.1	Energy Efficiency Index (EEI)	Energy Efficiency Index (EEI)	0.1	0.1	0.12	0.12	0.09	0.16
	Energy efficiency classe (ANNEX VI, (EU) No 874/20)	Energy efficiency class	A++	A++	A++	A++	A++	A+
3.1.2	(a) Nominal useful luminous flux displayed in a font at least twice as large as any display of the nominal lamp power;	---	70 Lm	35 Lm	35 Lm	45 Lm	70 Lm	90 Lm
	(b) Nominal life time of the lamp in hours (not longer than the rated life time);	Nominal life time	30,000H	30,000H	30,000H	30,000H	30,000H	30,000H
	(c) Colour temperature, as a value in Kelvins and also expressed graphically or in words;	Colour temperature	5000K	6000K	6500K	6100K	5000K	5000K
	(d) Number of switching cycles before premature failure;	Switch cycles	15,000 cycles	15,000 cycles	15,000 cycles	15,000 cycles	15,000 cycles	15,000 cycles
	(e) Warm-up time up to 60 % of the full light output (may be indicated as 'instant full light' if less than 1 second);	---	Pass	Pass	Pass	Pass	Pass	Pass
	(f) A warning if the lamp cannot be dimmed or can be dimmed only on specific dimmers; in the latter case a list of compatible dimmers shall be also provided on the manufacturer's website;	---	N/A	N/A	N/A	N/A	N/A	N/A
	(g) If designed for optimum use in non-standard conditions (such as ambient temperature $T_a \neq 25^\circ\text{C}$ or specific thermal management is necessary), information on those conditions;	---	Pass	Pass	Pass	Pass	Pass	Pass
	(h) Lamp dimensions in millimetres (length and largest diameter);	---	---	---	---	---	---	---
	(i) Nominal beam angle in degrees;	---	Max. 10	Max. 7	Max. 7	Max. 5	Max. 10	Max. 8
	(j) If the lamp's beam angle is $\geq 90^\circ$ and its useful luminous flux as defined in point 1.1 of this Annex is to be measured in a $120^\circ$ cone, a warning that the lamp is not suitable for accent lighting;	---	N/A	N/A	N/A	N/A	N/A	N/A
	(k) If the lamp cap is a standardised type also used with filament lamps, but the lamp's dimensions are different from the dimensions of the filament lamp(s) that the lamp is meant to replace, a drawing comparing the lamp's dimensions to the dimensions of the filament lamp(s) it replaces;	---	N/A	N/A	N/A	N/A	N/A	N/A
	(l) An indication that the lamp is of a type listed in the first column of Table 6 may be displayed only if the luminous flux of the lamp in a $90^\circ$ cone ( $\Phi 90^\circ$ ) is not lower than the reference luminous flux indicated in Table 6 for the smallest wattage among the lamps of the type concerned. The reference luminous flux shall be multiplied by the correction factor in Table 7. For LED lamps, it shall be in addition multiplied by the correction factor in Table 8;	---	N/A	N/A	N/A	N/A	N/A	N/A
	(m) An equivalence claim involving the power of a replaced lamp type may be displayed only if the lamp type is listed in Table 6 and if the luminous flux of the lamp in a $90^\circ$ cone ( $\Phi 90^\circ$ ) is not lower than the corresponding reference luminous flux in Table 6. The reference luminous flux shall be multiplied by the correction factor in Table 7. For LED lamps, it shall be in addition multiplied by the correction factor in Table 8. The intermediate values of both the luminous flux and the claimed equivalent lamp power (rounded to the nearest 1 W) shall be calculated by linear interpolation between the two	---	N/A	N/A	N/A	N/A	N/A	N/A
	(n) If the lamp contains mercury:	---	---	---	---	---	---	---
(o) Lamp mercury content as X,X mg;	---	N/A	N/A	N/A	N/A	N/A	N/A	
(p) Indication of which website to consult in case of accidental lamp breakage to find instructions on how to clean up the lamp debris.	---	N/A	N/A	N/A	N/A	N/A	N/A	
3.1.3	(a) The information specified in point 3.1.2	---	---	---	---	---	---	---
	(b) Rated power (0.1 W precision)	Rated power	1.6W	0.6W	0.6W	0.9W	1.45W	2.0W
	(c) Rated useful luminous flux	Luminous flux	70 Lm	35 Lm	35 Lm	45 Lm	70 Lm	90 Lm
	(d) Rated lamp life time	---	30,000H	30,000H	30,000H	30,000H	30,000H	30,000H
	(e) Lamp power factor	Power factor	1.0	1.0	1.0	1.0	1.0	1.0
	(f) Lumen maintenance factor at the end of the nominal life	Lumen maintenance factor	94.84%	93.83%	93.41%	87.71%	90.17%	90.05%
	(g) Starting time (as X,X seconds)	Starting time (s)	0.012	0.025	0.025	0.016	0.012	0.013
	(h) Colour rendering	Colour rendering	68.9	73.6	73.2	73.6	69.1	68.7
	(i) Colour consistency	Colour consistency	4.7	5.0	2.7	3.9	5.3	4.9
	(j) Rated peak intensity in candela (cd)	Peak intensity (cd)	2930	2986	2986	7525	2930	5880
	(k) Rated beam angle	Rated beam angle (degs.)	Max. 10	Max. 7	Max. 7	Max. 5	Max. 10	Max. 8
	(l) If intended for use in outdoor or industrial applications, an indication to this effect	---	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
	(m) Spectral power distribution in the range 180-800 nm	---	N/A	N/A	N/A	N/A	N/A	N/A
	(n) If the lamp contains mercury:	---	---	---	---	---	---	---
(o) Instructions on how to clean up the lamp debris in case of accidental lamp breakage;	---	N/A	N/A	N/A	N/A	N/A	N/A	
(p) Recommendations on how to dispose of the lamp at the end of its life for recycling in line with Directive 2012/19/EU of the European Parliament and of the Council ( 1 ).	---	N/A	N/A	N/A	N/A	N/A	N/A	

ANNEX III	Item	Item on Website	Model	Model	Model	Model	Model	Model
			DML801	DML802	DML803	DML805	DML806	DML807 (full output)
1.1	Energy Efficiency Index (EEI)	Energy Efficiency Index (EEI)	0.16	0.15	0.12	0.17	0.14	0.14
	Energy efficiency classe (ANNEX VI, (EU) No 874/20)	Energy efficiency class	A+	A+	A++	A+	A+	A+
3.1.2	(a) Nominal useful luminous flux displayed in a font at least twice as large as any display of the nominal lamp power;	---	270 Lm	185 Lm	200 Lm	750 Lm	680 Lm	680 Lm
	(b) Nominal life time of the lamp in hours (not longer than the rated life time);	Nominal life time	30,000H	30,000H	30,000H	30,000H	30,000H	30,000H
	(c) Colour temperature, as a value in Kelvins and also expressed graphically or in words;	Colour temperature	5000K	5000K	5000K	5000K	5000K	5000K
	(d) Number of switching cycles before premature failure;	Switch cycles	15,000 cycles	15,000 cycles	15,000 cycles	15,000 cycles	15,000 cycles	15,000 cycles
	(e) Warm-up time up to 60 % of the full light output (may be indicated as 'instant full light' if less than 1 second);	---	Pass	Pass	Pass	Pass	Pass	Pass
	(f) A warning if the lamp cannot be dimmed or can be dimmed only on specific dimmers; in the latter case a list of compatible dimmers shall be also provided on the manufacturer's website;	---	N/A	N/A	N/A	N/A	N/A	N/A
	(g) If designed for optimum use in non-standard conditions (such as ambient temperature $T_a \neq 25^\circ\text{C}$ or specific thermal management is necessary), information on those conditions;	---	Pass	Pass	N/A	N/A	N/A	N/A
	(h) Lamp dimensions in millimetres (length and largest diameter);	---	---	---	---	---	---	---
	(i) Nominal beam angle in degrees;	---	Max. 110	Max. 9	110	110	260	220
	(j) If the lamp's beam angle is $\geq 90^\circ$ and its useful luminous flux as defined in point 1.1 of this Annex is to be measured in a $120^\circ$ cone, a warning that the lamp is not suitable for accent lighting;	---	N/A	N/A	Pass	Pass	Pass	Pass
	(k) If the lamp cap is a standardised type also used with filament lamps, but the lamp's dimensions are different from the dimensions of the filament lamp(s) that the lamp is meant to replace, a drawing comparing the lamp's dimensions to the dimensions of the filament lamp(s) it replaces;	---	N/A	N/A	N/A	N/A	N/A	N/A
	(l) An indication that the lamp is of a type listed in the first column of Table 6 may be displayed only if the luminous flux of the lamp in a $90^\circ$ cone ( $\Phi 90^\circ$ ) is not lower than the reference luminous flux indicated in Table 6 for the smallest wattage among the lamps of the type concerned. The reference luminous flux shall be multiplied by the correction factor in Table 7. For LED lamps, it shall be in addition multiplied by the correction factor in Table 8;	---	N/A	N/A	N/A	N/A	N/A	N/A
	(m) An equivalence claim involving the power of a replaced lamp type may be displayed only if the lamp type is listed in Table 6 and if the luminous flux of the lamp in a $90^\circ$ cone ( $\Phi 90^\circ$ ) is not lower than the corresponding reference luminous flux in Table 6. The reference luminous flux shall be multiplied by the correction factor in Table 7. For LED lamps, it shall be in addition multiplied by the correction factor in Table 8. The intermediate values of both the luminous flux and the claimed equivalent lamp power (rounded to the nearest 1 W) shall be calculated by linear interpolation between the two	---	N/A	N/A	N/A	N/A	N/A	N/A
	(n) If the lamp contains mercury: Lamp mercury content as X,X mg;	---	---	N/A	N/A	N/A	---	---
(o) Indication of which website to consult in case of accidental lamp breakage to find instructions on how to clean up the lamp debris.	---	N/A	N/A	N/A	N/A	N/A	N/A	
3.1.3	(a) The information specified in point 3.1.2	---	---	---	---	---	---	---
	(b) Rated power (0.1 W precision)	Rated power	4.8W	3.6W	2.4W	12.0W	8.0W	8.0W
	(c) Rated useful luminous flux	Luminous flux	270 Lm	185 Lm	200 Lm	750 Lm	680 Lm	680 Lm
	(d) Rated lamp life time	---	30,000H	30,000H	30,000H	30,000H	30,000H	30,000 H
	(e) Lamp power factor	Power factor	1.0	1.0	1.0	1.0	1.0	1.0
	(f) Lumen maintenance factor at the end of the nominal life	Lumen maintenance factor	89.33%	92.50%	89.81%	93.74%	93.03%	91.28%
	(g) Starting time (as X,X seconds)	Starting time (s)	0.014	0.015	0.01	0.401	0.01	0.013
	(h) Colour rendering	Colour rendering	72.1	67.3	68.7	83.4	84.5	82.6
	(i) Colour consistency	Colour consistency	3.1	3.8	3.5	3.3	1.9	5.78
	(j) Rated peak intensity in candela (cd)	Peak intensity (cd)	100.8	9552	74.7	280	65.9	89
	(k) Rated beam angle	Rated beam angle (degs.)	Max. 110	Max. 9	110	110	260	220
	(l) If intended for use in outdoor or industrial applications, an indication to this effect	---	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
	(m) Spectral power distribution in the range 180-800 nm	---	N/A	N/A	N/A	N/A	N/A	N/A
	(n) If the lamp contains mercury: Instructions on how to clean up the lamp debris in case of accidental lamp breakage;	---	N/A	N/A	N/A	N/A	N/A	N/A
(o) Recommendations on how to dispose of the lamp at the end of its life for recycling in line with Directive 2012/19/EU of the European Parliament and of the Council ( 1 ).	---	N/A	N/A	N/A	N/A	N/A	N/A	

ANNEX III	Item	Item on Website	Model	Model	Model	Model	Model	Model
			DML807 (flashlight)	ML103	DML805 (110-130Vac)	ML104 (full output)	ML104 (flashlight)	ML105
1.1	Energy Efficiency Index (EEI)	Energy Efficiency Index (EEI)	0.126	0.11	0.16	0.14	0.11	0.131
	Energy efficiency classe (ANNEX VI, (EU) No 874/20)	Energy efficiency class	A++	A++	A+	A+	A++	A+
3.1.2	(a) Nominal useful luminous flux displayed in a font at least twice as large as any display of the nominal lamp power;	---	160 Lm	100 Lm	910 Lm	630 Lm	130 Lm	220Lm
	(b) Nominal life time of the lamp in hours (not longer than the rated life time);	Nominal life time	30,000H	30,000H	30,000H	30,000H	30,000H	30,000H
	(c) Colour temperature, as a value in Kelvins and also expressed graphically or in words;	Colour temperature	5,000K	5000K	5000K	5000K	5000K	5000K
	(d) Number of switching cycles before premature failure;	Switch cycles	15,000 cycles	15,000 cycles	15,000 cycles	15,000 cycles	15,000 cycles	15,000 cycles
	(e) Warm-up time up to 60 % of the full light output (may be indicated as 'instant full light' if less than 1 second);	---	Pass	Pass	Pass	Pass	Pass	Pass
	(f) A warning if the lamp cannot be dimmed or can be dimmed only on specific dimmers; in the latter case a list of compatible dimmers shall be also provided on the manufacturer's website;	---	N/A	N/A	N/A	N/A	N/A	N/A
	(g) If designed for optimum use in non-standard conditions (such as ambient temperature $T_a \neq 25^\circ\text{C}$ or specific thermal management is necessary), information on those conditions;	---	N/A	N/A	N/A	N/A	N/A	N/A
	(h) Lamp dimensions in millimetres (length and largest diameter);	---	---	---	---	---	---	---
	(i) Nominal beam angle in degrees;	---	20	80	110	340	20	7
	(j) If the lamp's beam angle is $\geq 90^\circ$ and its useful luminous flux as defined in point 1.1 of this Annex is to be measured in a $120^\circ$ cone, a warning that the lamp is not suitable for accent lighting;	---	Pass	Pass	Pass	Pass	Pass	Pass
	(k) If the lamp cap is a standardised type also used with filament lamps, but the lamp's dimensions are different from the dimensions of the filament lamp(s) that the lamp is meant to replace, a drawing comparing the lamp's dimensions to the dimensions of the filament lamp(s) it replaces;	---	N/A	N/A	N/A	N/A	N/A	N/A
	(l) An indication that the lamp is of a type listed in the first column of Table 6 may be displayed only if the luminous flux of the lamp in a $90^\circ$ cone ( $\Phi 90^\circ$ ) is not lower than the reference luminous flux indicated in Table 6 for the smallest wattage among the lamps of the type concerned. The reference luminous flux shall be multiplied by the correction factor in Table 7. For LED lamps, it shall be in addition multiplied by the correction factor in Table 8;	---	N/A	N/A	N/A	N/A	N/A	N/A
	(m) An equivalence claim involving the power of a replaced lamp type may be displayed only if the lamp type is listed in Table 6 and if the luminous flux of the lamp in a $90^\circ$ cone ( $\Phi 90^\circ$ ) is not lower than the corresponding reference luminous flux in Table 6. The reference luminous flux shall be multiplied by the correction factor in Table 7. For LED lamps, it shall be in addition multiplied by the correction factor in Table 8. The intermediate values of both the luminous flux and the claimed equivalent lamp power (rounded to the nearest 1 W) shall be calculated by linear interpolation between the two	---	N/A	N/A	N/A	N/A	N/A	N/A
	(n) If the lamp contains mercury: Lamp mercury content as X,X mg;	---	---	N/A	N/A	N/A	N/A	N/A
(o) Indication of which website to consult in case of accidental lamp breakage to find instructions on how to clean up the lamp debris.	---	N/A	N/A	N/A	N/A	N/A	N/A	N/A
3.1.3	(a) The information specified in point 3.1.2	---	---	---	---	---	---	---
	(b) Rated power (0.1 W precision)	Rated power	2.5W	1.5W	12.0W	9.5W	2.5W	3.7W
	(c) Rated useful luminous flux	Luminous flux	160 Lm	100 Lm	910 Lm	630 Lm	130 Lm	220Lm
	(d) Rated lamp life time	---	30,000 H	30,000H	30,000H	30,000H	30,000H	30,000H
	(e) Lamp power factor	Power factor	1.0	1.0	0.6	1.0	1.0	1.0
	(f) Lumen maintenance factor at the end of the nominal life	Lumen maintenance factor	90.98%	90.38%	89.65%	89.88%	91.50%	91.34%
	(g) Starting time (as X,X seconds)	Starting time (s)	0.013	0.017	0.471	0.015	0.013	0.015
	(h) Colour rendering	Colour rendering	84.52	86.29	83.22	84.51	85.49	85.11
	(i) Colour consistency	Colour consistency	4.15	3.98	2.62	2.39	4.17	2.09
	(j) Rated peak intensity in candela (cd)	Peak intensity (cd)	514	87.31	417.69	86.15	488.86	6820.75
	(k) Rated beam angle	Rated beam angle (degs.)	20	80	110	340	20	7
	(l) If intended for use in outdoor or industrial applications, an indication to this effect	---	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
	(m) Spectral power distribution in the range 180-800 nm	---	N/A	N/A	N/A	N/A	N/A	N/A
	(n) If the lamp contains mercury: Instructions on how to clean up the lamp debris in case of accidental lamp breakage;	---	N/A	N/A	N/A	N/A	N/A	N/A
(o) Recommendations on how to dispose of the lamp at the end of its life for recycling in line with Directive 2012/19/EU of the European Parliament and of the Council ( 1 ).	---	N/A	N/A	N/A	N/A	N/A	N/A	

ANNEX III	Item	Item on Website	Model	Model
			ML106	DML808
1.1	Energy Efficiency Index (EEI)	Energy Efficiency Index (EEI)	0.139	0.139
	Energy efficiency classe (ANNEX VI, (EU) No 874/20)	Energy efficiency class	A+	A+
3.1.2	(a) Nominal useful luminous flux displayed in a font at least twice as large as any display of the nominal lamp power;	---	220Lm	220Lm
	(b) Nominal life time of the lamp in hours (not longer than the rated life time);	Nominal life time	30,000H	30,000H
	(c) Colour temperature, as a value in Kelvins and also expressed graphically or in words;	Colour temperature	5000K	5000K
	(d) Number of switching cycles before premature failure;	Switch cycles	15,000 cycles	15,000 cycles
	(e) Warm-up time up to 60 % of the full light output (may be indicated as 'instant full light' if less than 1 second);	---	Pass	Pass
	(f) A warning if the lamp cannot be dimmed or can be dimmed only on specific dimmers; in the latter case a list of compatible dimmers shall be also provided on the manufacturer's website;	---	N/A	N/A
	(g) If designed for optimum use in non-standard conditions (such as ambient temperature $T_a \neq 25^\circ\text{C}$ or specific thermal management is necessary), information on those conditions;	---	N/A	N/A
	(h) Lamp dimensions in millimetres (length and largest diameter);	---	Pass	Pass
	(i) Nominal beam angle in degrees;	---	max. 70	max 65
	(j) If the lamp's beam angle is $\geq 90^\circ$ and its useful luminous flux as defined in point 1.1 of this Annex is to be measured in a $120^\circ$ cone, a warning that the lamp is not suitable for accent lighting;	---	N/A	N/A
	(k) If the lamp cap is a standardised type also used with filament lamps, but the lamp's dimensions are different from the dimensions of the filament lamp(s) that the lamp is meant to replace, a drawing comparing the lamp's dimensions to the dimensions of the filament lamp(s) it replaces;	---	N/A	N/A
	(l) An indication that the lamp is of a type listed in the first column of Table 6 may be displayed only if the luminous flux of the lamp in a $90^\circ$ cone ( $\Phi 90^\circ$ ) is not lower than the reference luminous flux indicated in Table 6 for the smallest wattage among the lamps of the type concerned. The reference luminous flux shall be multiplied by the correction factor in Table 7. For LED lamps, it shall be in addition multiplied by the correction factor in Table 8;	---	N/A	N/A
	(m) An equivalence claim involving the power of a replaced lamp type may be displayed only if the lamp type is listed in Table 6 and if the luminous flux of the lamp in a $90^\circ$ cone ( $\Phi 90^\circ$ ) is not lower than the corresponding reference luminous flux in Table 6. The reference luminous flux shall be multiplied by the correction factor in Table 7. For LED lamps, it shall be in addition multiplied by the correction factor in Table 8. The intermediate values of both the luminous flux and the claimed equivalent lamp power (rounded to the nearest 1 W) shall be calculated by linear interpolation between the two	---	N/A	N/A
	(n) If the lamp contains mercury: Lamp mercury content as X,X mg;	---	N/A	N/A
	(o) Indication of which website to consult in case of accidental lamp breakage to find instructions on how to clean up the lamp debris.	---	N/A	N/A
3.1.3	(a) The information specified in point 3.1.2	---	Pass	Pass
	(b) Rated power (0.1 W precision)	Rated power	3.6W	3.78W
	(c) Rated useful luminous flux	Luminous flux	220Lm	220Lm
	(d) Rated lamp life time	---	30,000H	30,000H
	(e) Lamp power factor	Power factor	1.0	1
	(f) Lumen maintenance factor at the end of the nominal life	Lumen maintenance factor	93.80%	93.94%
	(g) Starting time (as X,X seconds)	Starting time (s)	0.271	0.264
	(h) Colour rendering	Colour rendering	85.8	85.5
	(i) Colour consistency	Colour consistency	4.6	4.4
	(j) Rated peak intensity in candela (cd)	Peak intensity (cd)	251.8	275.3
	(k) Rated beam angle	Rated beam angle (degs.)	max.70	max. 65
	(l) If intended for use in outdoor or industrial applications, an indication to this effect	---	N/A	N/A
	(m) Spectral power distribution in the range 180-800 nm	---	Pass	Pass
	(n) If the lamp contains mercury: Instructions on how to clean up the lamp debris in case of accidental lamp breakage;	---	N/A	N/A
	(o) Recommendations on how to dispose of the lamp at the end of its life for recycling in line with Directive 2012/19/EU of the European Parliament and of the Council ( 1 ).	---	N/A	N/A

		Model BCF201	
Description	Symbol	Value	Unit
Maximum fan flow rate	F	16.99	m <sup>3</sup> /min
Fan power input	P	26.1	W
Service value	SV	0.65	(m <sup>3</sup> /min)/W
Standby power consumption	P <sub>SB</sub>	0.211	W
Fan sound power level	L <sub>WA</sub>	67.3	dB(A)
Maximum air velocity	C	2.32	m/sec
Measurement standard for service value	IEC 60879:1986 (coor.1992)		
Contact details for obtaining more information	Makita Europe N.V. Address: Jan-Baptist Vinkstraat 2 3070 Kortenber Phone: +32-(0)2-257-1840		

		Model DCF300	
Symbol	Value	Unit	
F	42.41	m <sup>3</sup> /min	
P	40.94	W	
SV	1.036	(m <sup>3</sup> /min)/W	
P <sub>SB</sub>	0.16	W	
L <sub>WA</sub>	62.18	dB(A)	
C	3.71	m/sec	
IEC 60879:1986			
Makita Europe N.V. Address: Jan-Baptist Vinkstraat 2 3070 Kortenber Phone: +32-(0)2-257-1840			

		Model CF100D	
Symbol	Value	Unit	
F	10	m <sup>3</sup> /min	
P	10	W	
SV	1	(m <sup>3</sup> /min)/W	
P <sub>SB</sub>	<0.1	W	
L <sub>WA</sub>	<58	dB(A)	
C	2.5	m/sec	
IEC 60879:1986			
Makita Europe N.V. Address: Jan-Baptist Vinkstraat 2 3070 Kortenber Phone: +32-(0)2-257-1840			

Description	Model CF101D			Model DCF102			Model DCF203		
	Symbol	Value	Unit	Symbol	Value	Unit	Symbol	Value	Unit
Maximum fan flow rate	F	7	m <sup>3</sup> /min	F	7	m <sup>3</sup> /min	F	18.9	m <sup>3</sup> /min
Fan power input	P	<12	W	P	<12	W	P	16	W
Service value	SV	0.7	(m <sup>3</sup> /min)/W	SV	0.7	(m <sup>3</sup> /min)/W	SV	1.2	(m <sup>3</sup> /min)/W
Standby power consumption	P <sub>SB</sub>	0	W	P <sub>SB</sub>	0	W	P <sub>SB</sub>	0.1	W
Fan sound power level	L <sub>WA</sub>	57	dB(A)	L <sub>WA</sub>	57	dB(A)	L <sub>WA</sub>	63	dB(A)
Maximum air velocity	C	3	m/sec	C	3	m/sec	C	2.9	m/sec
Measurement standard for service value	(EU) No 206/2012 + (EU) 2016/2282 EN 50564:2011 IEC 60879:1986 or EN ISO 5801:2017 EN 60704-1:2010+A11:2012 EN 60704-2-7:1998			(EU) No 206/2012 + (EU) 2016/2282 EN 50564:2011 IEC 60879:1986 or EN ISO 5801:2017 EN 60704-1:2010+A11:2012 EN 60704-2-7:1998			(EU) No 206/2012 + (EU) 2016/2282 EN 50564:2011 IEC 60879:1986 EN 60704-1:2010+A11:2012 EN 60704-2-7:1998		
Contact details for obtaining more information	Makita Europe N.V. Address: Jan-Baptist Vinkstraat 2 3070 Kortenber Phone: +32-(0)2-257-1840			Makita Europe N.V. Address: Jan-Baptist Vinkstraat 2 3070 Kortenber Phone: +32-(0)2-257-1840			Makita Europe N.V. Address: Jan-Baptist Vinkstraat 2 3070 Kortenber Phone: +32-(0)2-257-1840		

Model CF001G			
Description	Symbol	Value	Unit
Maximum fan flow rate	F	12.2	m <sup>3</sup> /min
Fan power input	P	13.27	W
Service value	SV	0.92	(m <sup>3</sup> /min)/W
Standby power consumption	P <sub>SB</sub>	0.13	W
Fan sound power level	L <sub>WA</sub>	55.7	dB(A)
Maximum air velocity	C	2.97	m/sec
Measurement standard for service value	2009/125/EC (EU) No 206/2012+ (EU) 2016/2282 IEC 60879:1986/COR1:1992 EN50564:2011 EN60704-2-7:1998 EN60704-1:2010+A11:2012		
Contact details for obtaining more information	Makita Europe N.V. Address: Jan-Baptist Vinkstraat 2 3070 Kortenber Phone: +32-(0)2-257-1840		

Model CF002G		
Symbol	Value	Unit
F	25.1	m <sup>3</sup> /min
P	23.6	W
SV	1.1	(m <sup>3</sup> /min)/W
P <sub>SB</sub>	0.1	W
L <sub>WA</sub>	61	dB(A)
C	4.1	m/sec
Measurement standard for service value	2009/125/EC (EU) No 206/2012 + (EU) 2016/2282 IEC 60879:1986/COR1:1992 EN 50564:2011 EN 60704-1:2010+A11:2012 EN IEC 60704-2-7:2020	
Contact details for obtaining more information		

Model DCF301		
Symbol	Value	Unit
F	24.2	m <sup>3</sup> /min
P	22.9	W
SV	1.1	(m <sup>3</sup> /min)/W
P <sub>SB</sub>	0.1	W
L <sub>WA</sub>	61	dB(A)
C	4	m/sec
Measurement standard for service value	2009/125/EC (EU) No 206/2012 + (EU) 2016/2282 IEC 60879:1986/COR1:1992 EN 50564:2011 EN 60704-1:2010+A11:2012 EN IEC 60704-2-7:2020	
Contact details for obtaining more information		

Model  
CF003G

Description	Symbol	Value	Unit
Maximum fan flow rate	F	96.5	m <sup>3</sup> /min
Fan power input	P	75.4	W
Service value	SV	1.3	(m <sup>3</sup> /min)/W
Standby power consumption	P <sub>SB</sub>	0.2	W
Fan sound power level	L <sub>WA</sub>	62	dB(A)
Maximum air velocity	C	3.4	m/sec
Measurement standard for service value	2009/125/EC (EU) No 206/2012 + (EU) 2016/2282 IEC 60879:2019 EN 50564:2011 EN IEC 60704-1:2021 EN IEC 60704-2-7:2020		
Contact details for obtaining more information			

Item	Model	Input voltage	Input AC frequency	output voltage	output current	output power	Average active efficiency	Efficiency at low load(10%)	No-load power consumption
1	DMR107	230V	50Hz	12V	700mA	8.4W	83.96%	76.92%	0.066W
2	DMR109 (DMR110)				1.0A	12.0W	86.27%	79.43%	0.080W
3	DMR106 DMR108 DMR112				1.2A	14.4W	86.67%	83.15%	0.064W
4	DMR114				2.5A	30W	88.32%	84.27%	0.073W
	DMR115								
5	DMR200				1.5A	18W	87.14%	83.30%	0.063W
	DMR201								
	DMR202								
	DMR203								